

Low Noise Power Supply R I S E 3 O-Wseries Specification

Equipped model (Manufactured by Cosel)	PBW30F-12	PBW30F-15
--	-----------	-----------

Specification

Series Name	RISE30-W12	RISE30-W15
Output Voltage ※4	±12V	±15V
Output Current	1.0A	0.8A
Maxium Output Power ※3	24W	24W

MODEL		RISE30-W12	RISE30-W15
Input	Voltage [V]	AC85~264 1φ or DC110~370	
	Current [A]	ACIN 100V	0.60typ
		ACIN 200V	0.35typ
	Frequency [Hz]	50/60 (47~440)	
	Efficiency [%]	ACIN 100V	72typ
		ACIN 200V	72typ
	Inrush Current [A]	ACIN 100V	15typ (I _o =100%) (Cold Start)
Output		ACIN 200V	30typ (I _o =100%) (Cold Start)
	Leakage Current [mA]	0.30/0.65 max (ACIN 100V/240V 60Hz, I _o =100%, Mesure with IEC60950-1)	
	Nominal Voltage [V]	±12	±15
	Nominal Current [A]	1.0	0.8
	Line Regulation [mV] ※6	60max	60max
	Load Reguration [mV] ※7	100max	100max
	Ripple [mVp-p] ※1	2typ	2typ
	Ripple Noise [mVp-p] ※1	5typ	5typ
	Operating Temperature Change [mV]	120max (0°C~+50°C)	150max (0°C~+50°C)
	Warm-Up Drift [mV] ※2	48max	60max
	Start-up Time [ms]	200typ (ACIN 100V, I _o =100%) ※700typ : when you turn the power supply ON/OFF repeatedly that interval less than 1minute.	
	Hold-up Time [ms]	20typ (ACIN 100V, I _o =100%)	
Additional Function	Output Voltage Range [V] ※8	11.4~12.6(+V, -V Simultaneous change)	14.25~15.75(+V, -V Simultaneous change)
	Voltage Setting Accuracy [V]	11.7~12.3 (+V, -V Nominal Current)	14.7~15.3 (+V, -V Nominal Current)
	Over Current Protection	Start at 105% at Nominal Current、Auto - recovery	
Isolation	Over Voltage Protection [V]	16.80~24.00	20.00~29.00
	Running Indicate	LED Indicator : Green	
	Input - Output	AC3,000V 1min Cut off Current =over 10mA, DC500V 50MΩ (Normal temperature / humidity)	
Enviromental Condition	Input - FG	AC2,000V 1min Cut off Current =over 10mA, DC500V 50MΩ (Normal temperature / humidity)	
	Output - FG	AC500V 1min Cut off Current = over 100mA, DC500V 50MΩ (Normal temperature / humidity)	
	Operating Temperature / Humidity	-10~+60°C(With output) , 20~90%RH (Non Condensing)	
	Strage Temperature / Humidity	-20~+75°C, 20~90%RH (Non Condensing)	
Others ※5	Vibration Resistance	10~55Hz 19.6m/s ² (2G) period 3min, 1hour for X, Y, Z direction	
	Shock Resistance	196.1m/s ² (20G) 11ms 1time for X, Y, Z, direction	
	Safety Standard (Compliance)	UL60950-1, C-UL(CSA60950-1), EN60950-1, EN50178 , PSE Compliance	
Structure	Conducted Emission (Compliance)	FCC Part15 classB, VCCI-B, CISPR22-B, EN55011-B, EN55022-B Compliance	
	Harmonic Current Characteristics	IEC61000-3-2 Compliance[A power factor improvement circuit (active filter) is not built-in.※5]	
	Size (W x H x D), Weight	W34.5 x H124 x D103mm (Without terminal standard) / 500g max	
	Cooling System	Convection	

※1 Measured by 20MHZ oscilloscope or Ripple-Noise meter(Equivalent to KEISOKU-GIKEN: RM101)

※2 Drift is the change in DC output for an eight hour period after a half-hour warm-up at 25°C

※3 The sum of +power -power must be less than output power

※4 ±12V, ±15V can be used as +24 and +30V but specification of output will change. Please contact us for detail.

※5 Applied for PBW(Cosel) itself. If you use multiple units for a single system, standards may not be satisfied.

※6 When the input voltage changes suddenly, the output voltage accuracy might exceed the specification.

※7 Other side's current (Non-measurement side) is fixed

※8 The case use only single output, output voltage range has possibility to be change.

※ Do not use this power supply unit under overload state or outside of its nominal intended use that will cause damage or malfunctions.

※ Derating is required

※ Parallel operation with other model is not possible

※ A sound may occur from power supply at peak loading.



רכישה בישראל:

072-2332263

www.4niev.com